Material Safety Data Sheet

Product Name: D203 (New product name – D890), Cl form Macroporous, Strong BaseType 1 Porous Anion Exchange Resin Effective date: 10/01/06

Company Address:

General Technologies, SPC 14200 Hadley St. Overland Park, KS 66223

Information Numbers:

Emergency

Phone Number: 913-766-5566 / 816-590-9631 (evenings & weekends) Fax Number: 253-663-9333 Email: info@gtspc.com Website: http://gtspc.com

1. Ingredients:

Triethylamine functionalized, chloromethylated

Copolymer of styrene and divinylbenzene in the	
--	--

chloride form	CAS# 063453-90-7
Water	CAS# 007732-18-5

This document is prepared pursuant to the OSHA Hazard Communication Standard (29CFR 1910.1200) . In Addition, other substances not hazardous per this OSHA Standard may be listed. Where proprietary ingredient Shows, the identity may be made available as provided in this standard.

2. Physical / Chemical Data:

Boiling Point:	Not Applicable
Vapor Pressure (MM HG): Not Applicable	
Evaporation Rate (water = 1): 1	
Appearance & Odor:	Light cream to light yellow may have amine odor.
Specific Gravity:	1.2 (water = 1)
Melting Point (deg. F)	NotApplicable
Solubility in Water :	Insoluble
Thermal:	May yield oxides of carbon and nitrogen
Vapor Density:	NotApplicable

Product Hazard Rating	Scale
Toxicity = 0	0 = Negligible
Fire = 0	1 = Slight
Reactivity = 0	2 = Moderate
Special N/A	3 = High
	4 = Extreme

3. Fire & Explosion Hazard Data

Flammable Limits:	800 ⁰ Deg. F	
Unusual Fire & Explosion Haz	zards: Product is not combustible until moisture is removed, Then resin starts to burn in	
flame at 230 C. Autoignition occurs above 500C. Possible fire.		
Combustion Products:	Hazardous combustion products may include and are not Limited to : hydrocarbons,	
	sulfur oxides, organic sulfonates, Carbon monoxide, carbon dioxide, benzene compounds.	
Extinguishing Media:	Water, CO2, Talc, Dry Chemical	
Special Fire Fighting Procedures: MSHA / NIOSH approved self-contained breathing gear.		

4. Reactivity Data

Stability:	Stable	
Conditions to Avoid:	Temperatures above 400 [°] F	
Hazardous by Products:	See Section 3 above for possible combustion products.	
Materials to avoid contact with: Strong oxidizing agents (i.e. nitric acid)		
Hazardous Polymerization: Material does not polymerize		
Storage: Store in a cool dry place		
5. Health Hazards & Sara (Right to Know)		
Emergency First Aid Pro	ocedures: Contact with eyes can and skins can cause irritation.	
Skin Absorption: Skin absorption is unlikely due to physical properties.		
Ingestion:	Single dose oral LD50 has not been determined. Single Does oral toxicity is believed to be low.	
No hazards anticipated from ingestion incidental to industrial exposure.		
Inhalation: Vapors are unlikely due to physical properties.		
Systemic & Other Effects: No specific data available, however, repeated exposures are not		
anticipated to cause any significant adverse effects.		
Carcinogenicity: Not Applicable		
Sara title 3, sections 311 & 312: All ingredients are non-hazardous		
6. First Aid		
Eyes :	irrigate immediately with water for at least 5 minutes. Mechanical irritation only.	
Skin:	No adverse effects anticipated by this route of exposure.	
Ingestion:	No a dverse effects anticipated by this route of exposure incidental to proper industrial	
Ha	indling.	
Inhalation:	No adverse effects anticipated by this route of exposure.	

7. Control Measures

Respiratory protecti	on: Not required for normal uses if irritation occurs from breathing-get fresh air!	
Eye protection:	Splash goggles	
Ventilation:	Normal	
Protective Gloves:	Not required.	
8. Safe handling pro	cedures	
In Case of Spills:	Sweep up material and transfer to containers. Use caution the floor will be slippery!	
Disposal Method:	Bury resin licensed landfill or burn in approved incinerator according to local, state,	
	and federal regulations. For resin contaminated with hazardous material, dispose of	
	mixture as hazardous material according to local, state and federal regulations.	
9. Additional Inform	ation:	
Special precautions		
taken in handling a		
	feed, regenerant, resin form, and effluent of that process.	
TSCA Considerati	ONS: Every different salt or ionic form of an ionexchange resin is a separate chemical. If	
	you use an ion-exchange resin for ion-exchange purposes and then remove the by-	
	product resin from its vessel or container prior to recovery of the original or another	
	form of the resin or of another chemical, the by-product resin must be listed on the	
	TSCA Inventory (unless an exemption is applicable). It is the responsibility of the	
	customer to ensure that such isolated, recycled by-product resins are in compliance	
	with TSCA. Failure to comply could result in substantial civil or criminal penalties	
	being assessed by the Environmental Production Agency.	
MSDS Status:	Canadian regulatory information added.	
10. Regulatory Inform	mation: (Not meant to be all-inclusive-selected regulations represented.)	
Notice:	The information herein is presented in good faith and believed to be accurate as of the	
	effective date shown above. However, no warranty, express or implied, is given.	
	Regulatory requirements are subject to change and may differ from one location to	
	another, it is the buyer responsibility to ensure that its activities comply with federal,	
state or provincial, and local laws. The following specific information is made for the		
	purpose of complying with numerous federal, state or provincial, and local laws and	
	regulations. See MSDS Sheet for health and safety information.	
11. Canadian Regula	tions:	
WHMIS Imformat	ion: The Canadian Workplace Hazardous Materials Information System (WHMIS)	
	Classification for this product is:	
	This product is not controlled Product under WHMIS.	
Canadian TDG Info	ormation: For guidance, the Transportation of Dangerous Good Classification for this product is	
	Not regulated.	