

# GENERAL TECHNOLOGIES, SPC

- High-Quality Services & Products

产品介绍 Products

## STANDARD-DESIGN RO SYSTEMS



### SINGLE-PASS RO SYSTEMS

MODEL NO.	CAPACITY m <sup>3</sup> /h	MOTOR kw	SALT REJECT %	FEED WATER mm	CONCENTRATE mm	PERMEATE mm	SKID DIMENSION mm
HL-RO-0.5	0.5	1.1	≥97	DN20	DN20	DN20	1600x600x1500
HL-RO-01	1.0	2.2	≥97	DN25	DN25	DN25	2600x800x1500
HL-RO-02	2.0	4.0	≥97	DN32	DN32	DN32	2600x800x1500
HL-RO-03	3.0	4.0	≥97	DN32	DN32	DN32	2800x800x1500
HL-RO-05	5.0	7.5	≥97	DN40	DN40	DN40	3800x800x1750
HL-RO-06	6.0	7.5	≥97	DN40	DN40	DN40	4800x800x1750
HL-RO-08	8.0	11.0	≥97	DN50	DN50	DN50	3800x800x1750
HL-RO-10	10.0	15.0	≥97	DN50	DN50	DN50	4800x800x1750



### DOUBLE-PASS RO SYSTEMS

MODEL NO.	CAPACITY M <sup>3</sup> /h	MOTOR kw	SALT REJECT %	FEED WATER mm	CONCENTRATE mm	PERMEATE mm	SKID DIMENSION mm
HL-RO-0.5	0.5	1.1	≥99.5	DN25	DN20	DN20	1600x600x1500
HL-RO-01	1.0	4.4	≥99.5	DN40	DN32	DN32	2600x800x1500
HL-RO-02	2.0	7.0	≥99.5	DN40	DN32	DN32	3800x900x1800
HL-RO-03	3.0	8.0	≥99.5	DN40	DN32	DN32	3800x1200x1700
HL-RO-06	6.0	18.5	≥99.5	DN50	DN50	DN50	4800x1250x1750
HL-RO-10	10.0	26.0	≥99.5	DN65	DN50	DN50	4800x1500x1750

GENERAL TECHNOLOGIES, SPC  
 - High-quality Services & Products  
 Tel: 816-590-9641  
 Fax: 253-663-9333  
 Email: [sales@gtspc.com](mailto:sales@gtspc.com)